



Elevator Equipment Corporation

4035 Goodwin Avenue, Los Angeles, CA 90039 - (800) 423-2800

2230 N.W. 12th Street, Richmond, IN 47374 - (800) 428-6564

LA Fax: (323) 245-9771 - Richmond, IN Fax: (765) 966-7299

www.elevatorequipment.com and www.eecovalves.com

# UV-4R Quotation & Order Form

Request For Quote     Order, PO # \_\_\_\_\_

Company \_\_\_\_\_ Telephone (    ) \_\_\_\_\_

Contact \_\_\_\_\_ Fax (    ) \_\_\_\_\_

Company Address \_\_\_\_\_ E-mail Address \_\_\_\_\_

City \_\_\_\_\_ State \_\_\_\_\_ Zip \_\_\_\_\_ Today's Date \_\_\_\_\_ Date Required \_\_\_\_\_

Project Name \_\_\_\_\_

1. Quantity Required <sup>2</sup>

2. Coil Voltage <sup>2</sup>

3. Existing valve (If any): EECO UV-4R (Size)   
Other (Mfg, model, size)

4. Static Pressure <sup>1</sup>  or Empty Car Weight (lbs)   
(psi), Empty car at bottom landing. Plunger Diameter (in)   
or Circumference (in)

5. Flow Rate (GPM) <sup>1</sup>  or Car Speed (FPM) Up   
Also need plunger info in #4 above. Down   
If different

6. Max Operating Pressure (psi)  or Capacity (lbs)   
Also need empty car weight info in #4 above.

7. Total Travel (ft)

8. Line Connections  
3/4" NPT <sup>3</sup> is the only option for all three ports

9. 0-1000 psi Liquid Filled Pressure Gage <sup>4</sup> Yes  No

10. Pressure Gage Quick Disconnect <sup>4</sup> Jack  Pump

11. Pressure Gage Connection with Shut Off Valve <sup>4</sup> Yes  No

12. 90° 1/8" Male to Male Elbow Yes  No

13. Low Pressure Switch <sup>4</sup> Yes  No

14. Dual voltage down leveling coil for emergency (battery backup) lowering <sup>4</sup> Yes  No

<sup>1</sup> Required for sizing, <sup>2</sup> Required, <sup>3</sup> Standard, <sup>4</sup> Optional

Please fax this form to EECO at (323) 245-9771



The EECO UV-4R four coil residential control valve.



UV-4R shown on the EECO residential power unit.



Optional 0-1000 psi liquid filled pressure gage, 1/8" Male NPT, P/N P10200

Optional 1/8" female NPT to female quick connect/disconnect fitting, P/N P10201

Optional 1/8" female NPT to male quick connect/disconnect fitting, P/N P10202

Optional 90° 1/8" NPT elbow male to male, P/N P10205



Optional 1/8" NPT male to male hex nipple, P/N P10203

Optional 1/8" NPT male to male shut off valve, P/N P10204