



Elevator Equipment Corporation

4035 Goodwin Avenue, Los Angeles, CA 90039 - (800) 423-2800

2230 N.W. 12th Street, Richmond, IN 47374 - (800) 428-6564

LA Fax: (323) 245-9771 - Richmond, IN Fax: (765) 966-7299

www.elevatorequipment.com and www.eecovalves.com

UV-5AT & UV-5ATC Quotation & Order Form

Request For Quote Order, PO # _____

Company _____ Telephone () _____

Contact _____ Fax () _____

Company Address _____ E-mail Address _____

City _____ State _____ Zip _____ Today's Date _____ Date Required _____

Project Name _____

1. Quantity Required ²

2. Coil Voltage ²

3. Existing valve (If any): EECO UV-5A (Size)
Other (Mfg, model, size)

4. Static Pressure ¹ or Empty Car Weight (lbs)
(psi), Empty car at bottom landing.
Plunger Diameter (in)
or Circumference (in)

5. Flow Rate (GPM) ¹ or Car Speed (FPM) Up
Also need plunger info in #4 above. Down
if different

6. Max Operating Pressure (psi) or Capacity (lbs)
Required for UV-5ATC. Also need empty car weight info in #4 above.

7. Total Travel (ft)

8. Line Connections ² Pump Jack Return
2" NPT ³
2" Grooved ⁴

9. Jack Port Left Hand ³ Right Hand ⁴ (Contact EECO)

10. Constant Down Speed (UV-5ATC) ⁴ Yes No

11. 0-1000 psi Liquid Filled Pressure Gage ⁴ Yes No

12. Pressure Gage Quick Disconnect ⁴ Jack Pump

13. Pressure Gage Connection with Shut Off Valve ⁴ Yes No

14. 90° 1/8" Male to Male Elbow Yes No

15. Low Pressure Switch ⁴ Yes No

16. Modified Down Piston To Close At Low Pressure (less than 50 psi) ⁴ Yes No

17. Dual voltage down leveling coil for emergency (battery backup) lowering ⁴ Yes No

¹ Required for sizing, ² Required, ³ Standard, ⁴ Optional

Please fax this form to EECO at (323) 245-9771


UV-5AT



UV-5A with optional
2" grooved jack/return connections,
P/N 5366
2" grooved pump inlet connection,
P/N 5231-VC



Optional Low Pressure Switch,
N.O.: P/N 5253,
N.O./N.C.: P/N 5245



Optional right hand jack
port adapter, P/N 5620A



Optional 0-1000 psi
liquid filled pressure
gage, 1/8" Male NPT,
P/N P10200

Optional 1/8" female
NPT to female quick
connect/disconnect
fitting, P/N P10201



Optional 1/8" female NPT to male
quick connect/disconnect fitting,
P/N P10202



Optional 90°
1/8" NPT elbow
male to male,
P/N P10205



Optional 1/8" NPT
male to male hex
nipple, P/N P10203

Optional 1/8" NPT male
to male shut off valve,
P/N P10204